

MEASUREMENT CHART FOR MISSY & WOMAN FULL BODY FORMS

Unit: Inch

Position \ Specification	2	4	6	7	8	9	10	12	14	16	18	20
TOTALNECK	12 1/2	12 1/2	13	12 1/2	13 1/2	13	14	14 1/2	15	15 1/2	16 1/2	17
BUST	32 1/2	33 1/2	34 1/2	34 1/2	35 1/2	35 1/2	36 1/2	38	39 1/2	41	43 1/2	47
WAIST	24 1/2	25	25 1/2	25	26 1/2	26	27 1/2	29	30 1/2	32	34 1/2	40 1/2
HIP	34 1/2	35	35 1/2	36	36 1/2	37	37 1/2	39	40 1/2	42	45	48
SHOULDER	4 3/4	4 7/8	5	4 13/16	5 1/8	5	5 1/4	5 7/16	5 10/16	5 13/16	6	6 1/4
ACROSS BUST	6 1/2	6 3/4	6 7/8	7	7	7 1/8	7 1/8	7 1/4	7 1/2	8	8 1/2	9 1/2
X-BACK	13 1/4	13 3/4	14	13 5/8	14 1/4	19	14 1/2	14 7/8	15 1/4	15 5/8	16	16 1/4
NK.TO.FT.WT	13 3/4	14	14 1/4	13 3/4	14 1/2	14	14 3/4	15	15 1/4	15 1/2	15 3/4	16
NK.TO.BK.WT	15 3/4	16	16 1/4	15 3/4	16 1/2	16	16 3/4	17	17 1/4	17 1/2	17 3/4	18
TOTALCROTCH	24 1/2	24 1/2	25	25 1/2	25 1/2	26	26	26 1/2	27	27 1/2	30	32
MAX.THIGH	19	19 1/2	20	20 1/8	20 3/4	20 3/4	21 1/2	22 1/2	23 1/2	24 1/2	27	29
KNEE	12 3/4	13	13 1/4	13	13 5/8	13 1/2	14	14 1/2	15	15 1/2	17 1/2	19
CALF	10 3/4	11 1/2	12 1/4	12	12 5/8	12 1/2	13	13 1/2	14	14 1/2	16 1/2	18
ANKLE	9	9 1/4	9 1/2	9 1/2	9 3/4	9 3/4	10	10 1/4	10 1/2	10 3/4	11	11 1/4
WT.TO ANKLE	38 1/2	38 3/4	39	39 1/4	39 1/4	39 1/2	39 1/2	39 3/4	40	40 1/2	41	41

FAQ

1. Sometimes after a few years of using the form, the tube inside dress form torso may get worn, causing the torso drops down easily, if this happens, you need do a little adjustment around the two triangle metals, Unscrew the little nut on the top triangle metal, and screw down the top triangle metal a little bit, then screw down and tight that nut, this way moves the two triangle metals closer and enlarge the outer shape to hold the torso well.
2. Sometimes the pole gets stuck inside the tube, this may happen because the customer is not familiar with the installation of the pole; she may forget to put the big spring in the bottom of the pole to prevent the torso dropping down to the end, if the pole gets stuck inside the tube of the torso and you can't pull it out, use tool like plier to unscrew the 2 little nuts on the tiny end, then pull out all the pole parts one by one and reinstall them again.

